

Dimensions and Weight

| | |
|----------------------------------|--|
| Model | EU20i |
| Power equipment description code | EAAJ |
| Length x Width x Height | 510 x 290 x 425 mm (20.1 x 11.4 x 16.7 in) |
| Dry weight | 21 kg (46.3 lb) |

Engine

| | |
|------------------------------|--|
| Model | GX100 |
| Engine type | 4-stroke, overhead camshaft, single cylinder |
| Displacement (Bore x Stroke) | 98 cc (6.0 cu in) [56.0 x 40.0 mm (2.20 in x 1.57 in)] |
| Compression ratio | 8.5 : 1 |
| Engine speed | 4,300 – 5,000 r.p.m. (with eco throttle switch OFF) |
| Cooling system | Forced air |
| Ignition system | Full transistor |
| Oil capacity | 0.40 ℓ (0.42 US qt, 0.35 Imp qt) |
| Fuel tank capacity | 4.1 ℓ (1.08 US gal, 0.90 Imp gal) |
| Spark plug | CR5HSB (NGK) |

Generator

| | | |
|----------------------|--|--|
| Model | EU 20i | |
| Type | G, B, F, W U | |
| Rated Voltage (V) | 230 240 | |
| Rated Frequency (Hz) | 50 | |
| Rated Ampere (A) | 7.0 6.7 | |
| Rated Output (VA) | 1,600 | |
| Max Output (VA) | 2,000 | |
| DC output | Only for charging 12 V automotive batteries. Maximum charging output = 8A | |