

## POWERCENTER 15 GENERATOR

### ALTERNATOR

Three Phase	Rated Output	(kVA)	15
	Rated Voltage	(V)	415
	Rated Current	(A)	20.9
	Power Factor		0.8
Single Phase	Rated Output	(kVA)	15/12
	Rated Voltage	(V)	240/110
	Rated Current	(A)	50/109.1
	Power Factor		1.0
Rated Frequency		(Hz)	50
Excitation			Brushless
Number of Poles			2

- Fully bundled
- Multi-voltage
- Super silent
- Compact design

### ENGINE

Model	(Kubota)	D902
Rated Speed	(min-1)	3000
Fuel		Diesel
Fuel Tank Capacity	(L)	37
Fuel Consumption	(L/Hr)	3.5
Lubricant Capacity	(L)	3.6
Coolant Capacity	(L)	4.0

### SET

Dry Weight	(kg)	390
Length	(mm)	1,410
Width	(mm)	635
Height	(mm)	780
Noise	(dB*A/7m)	63.5
	(LWA*dB)	91.5
Bunded		YES
Emergency Stop		YES
Digital Display		YES
Outputs	Three Phase	(415V) 1 x 32Amp
	Single Phase	(240V) 2 x 32Amp 1 x 16Amp
	Single Phase	(110V) 2 x 32Amp 1 x 16Amp
	Hard Wire/Terminal Board	YES

